

US Serial No. 10/687,905  
Reply to Advisory Action of August 2, 2006  
Page 2 of 6

RECEIVED  
CENTRAL FAX CENTER  
SEP 05 2006

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

**Claim 1 (Canceled)**

**Claim 2 (Canceled)**

**Claim 3 (Currently Amended)** ~~The device of claim 2~~ A device for detecting presence of a child restraint seat when the child restraint seat is attached to a vehicle seat, the device comprising:

an anchorage having at least one coupler adapted to couple with a complementary coupler on the child restraint seat to retain the child restraint seat on the vehicle seat; the anchorage being movable with respect to the vehicle seat and being biased to a first position with respect to the vehicle seat, the first position being indicative of an absence of a child restraint seat attached to the anchorage, and

a position sensor attached to the anchorage for detecting movement of the anchorage to a second position with respect to the seat, thereby indicating a child restraint seat is attached to the anchorage, the position sensor being adapted to transmit a signal to an air bag controller when moved to the second position;

wherein the anchorage is biased to the first position by at least one spring and is pivotally mounted with respect to the seat and rotates from the first position to the second position

**Claim 4 (Canceled)**

**Claim 5 (Currently Amended)** The device of claim ~~4~~ 3 wherein the vehicle seat includes a seat back frame, the anchorage being attached to the seat back frame by a cross bar adapted to be mounted between two vertically extending seat back frame members comprising the seat back frame.

US Serial No. 10/687,905  
Reply to Advisory Action of August 2, 2006  
Page 3 of 6

RECEIVED  
CENTRAL FAX CENTER

SEP 05 2006

**Claim 6 (Original)** The device of claim 5 wherein the anchorage comprises an anchorage bar extending along the cross bar and having two couplers at spaced locations thereon.

**Claim 7 (Original)** The device of claim 6 wherein the anchorage bar is resilient and is fixed to the cross bar at a portion of the anchorage bar, a second portion of the anchorage bar having the couplers thereon and being deflectable with respect to the first portion.

**Claim 8 (Original)** The device of claim 7 wherein the couplers are loops disposed adjacent to opposite ends of the anchorage bar.

**Claim 9 (Original)** The device of claim 8 wherein the cross bar has a load limiter surface thereon which engages the anchorage bar when the bar deflects to the second position.

**Claim 10 (Original)** The device of claim 9 wherein the position sensor is mounted on a plate extending between the loops that define the couplers.

**Claim 11 (Currently Amended)** ~~The device of claim 6~~ A device for detecting presence of a child restraint seat when the child restraint seat is attached to a vehicle seat, the device comprising:

an anchorage having at least one coupler adapted to couple with a complementary coupler on the child restraint seat to retain the child restraint seat on the vehicle seat; the anchorage being movable with respect to the vehicle seat and being biased to a first position with respect to the vehicle seat, the first position being indicative of an absence of a child restraint seat attached to the anchorage, and

a position sensor attached to the anchorage for detecting movement of the anchorage to a second position with respect to the seat, thereby indicating a child restraint seat is attached to the anchorage, the position sensor being adapted to transmit a signal to an air bag controller when moved to the second position;

US Serial No. 10/687,905  
Reply to Advisory Action of August 2, 2006  
Page 4 of 6

wherein the vehicle seat includes a seat back frame, the anchorage being attached to the seat back frame by a cross bar adapted to be mounted between two vertically extending seat back frame members comprising the seat back frame;

wherein the anchorage comprises an anchorage bar extending along the cross bar and having two couplers at spaced locations thereon;

wherein the anchorage bar has a first portion pivotally mounted on the cross bar and wherein at least one spring is disposed between the anchorage bar and cross bar urging the anchorage bar to the first position.

**Claim 12 (Original)** The device of claim 11 wherein the couplers are loops disposed at opposite ends of the anchorage bar.

**Claim 13 (Original)** The device of claim 12 wherein the cross bar has a load limiter surface thereon which engages the anchorage bar when the bar deflects to the second position.

**Claim 14 (Original)** The device of claim 13 wherein the position sensor is mounted on a plate extending between the loops that define the couplers.

**Claim 15 (Currently Amended)** A device for detecting a presence of a child restraint seat when the child restraint seat is attached to a vehicle seat having a seat back frame that includes a pair of side frame members that are horizontally spaced from one another, the device comprising:

a cross bar having first and second ends, the first and second ends being fixed to the first and second side frame members, respectively, of the seat back frame;

an anchorage bar mounted on the cross bar and having first and second couplers thereon for coupling with couplers on the child restraint seat to retain the child restraint seat on the vehicle seat; the anchorage bar being movable with respect to the cross bar from a first position to a second position and being biased to the first position,

US Serial No. 10/687,905  
Reply to Advisory Action of August 2, 2006  
Page 5 of 6

wherein the anchorage bar has a first portion pivotally mounted on the cross bar and wherein at least one spring is disposed between the anchorage bar and cross bar for urging the anchorage bar to the first position; and

a position sensor attached to the anchorage bar for detecting movement of the anchorage bar to the second position indicative of a child restraint seat being coupled to the anchorage bar, the position sensor being adapted to transmit a signal to an air bag controller when moved to the second position indicating the presence of the child restraint seat on the vehicle seat

**Claim 16 (Original)** The device of claim 15 wherein the couplers are loops disposed at opposite ends of the anchorage bar.

**Claim 17 (Original)** The device of claim 16 wherein the cross bar has a load limiter surface thereon which engages the anchorage bar when the anchorage bar deflects to the second position.

**Claim 18 (Original)** The device of claim 17 wherein the position sensor is mounted on a plate extending between the loops that define the couplers.

**Claim 19 (Original)** The device of claim 15 wherein the anchorage bar is resilient and is fixed to the cross bar at a portion of the anchorage bar, a second portion of the anchorage bar having the couplers thereon and being deflectable with respect to the first portion.

**Claim 20 (Canceled)**